



# PureLink™ Water Purification System

## Pool & Spa Control and Water Purification All in One!

The Jandy PureLink™ integrates the award winning AquaLink® RS Control System with Jandy's state-of-the-art AquaPure™ salt chlorine generation system in one Power Center. With the addition of the PureLink Cell Kit and any of Jandy's AquaLink RS Controllers — PDA, OneTouch or All Button — you'll have complete control over your backyard paradise. Activate and program all your pool and spa features as your water is naturally purified. Pool and spa control and purification all in one with PureLink.

**Integrated AquaPure and AquaLink RS for easy and cost effective installation.**

### INTEGRATED AT LAST

**AquaLink® RS**  
+ **AquaPure**  
= **PureLink**

An AquaPure System integrated into an AquaLink RS Power Center, ready to accept the AquaLink RS control of your choice. Jandy brings together the power of AquaLink with the peace of mind of AquaPure.

### CRYSTAL CLEAR WATER PURIFICATION



The AquaPure Chlorine Generation system provides trouble free, accurate and safe water purification through a process that converts salt into the chlorine needed to sanitize your pool and spa water.

### THE POWER AND EASE OF AQUALINK RS



From any AquaLink RS remote, you can adjust water purification levels with feedback on salinity levels. Of course, complete control of all your pool and spa features is at your fingertips as well.

### PLUG-AND-PLAY INSTALLATION



With only one Power Center to wire, installation is simple and cost effective. All electronics are incorporated and pre-wired. Just plumb the AquaPure Cell Kit and control everything from your AquaLink RS Controller.



# AquaPure™ + AquaLink® RS = PureLink™

The PureLink incorporates the AquaPure Water Purification System electronics into the AquaLink RS Power Center for a simple and convenient installation. Add the benefits of water purification to your pool and spa control system with a PureLink Standard or Sub-Panel Power Center.

## PUT TOGETHER THE PERFECT SYSTEM

### PureLink Power Center

The PureLink all-in-one Power Center incorporates the AquaPure PCBs and transformer into the AquaLink RS Power Center for installation convenience. The PureLink Power Center is available for pools up to 40,000 gallons.

### PureLink 3-Port Cell Kit (sold separately)

The PureLink Cell Kit contains the cell, sensor and cables necessary for plug-and-play installation into the PureLink Power Center. The new 3-port cell allows plumbing flexibility plus integrates a slotted, non threaded sensor into the cell, uses Jandy universal 2"-2.5" unions, and includes a self cleaning kit.



### AquaLink RS Control System (sold separately)

The AquaLink RS System contains the controller, sensors and PCB for plug-and-play installation into the PureLink Power Center.



## CONTROL FROM AQUALINK RS

PDA, OneTouch or All Button Controllers fully integrate with the Jandy chlorine generators through the new PureLink Power Center.

Water Purification levels can be controlled from the main menu of the AquaLink RS Controller (All Button, OneTouch, or PDA) or may be adjusted from the PureLink Power Center while the AquaLink RS is online. Boost chlorine production and monitor purification levels from the wired or wireless handheld controller.

Take control of your backyard paradise and rest assured that your water is sparkling clean with PureLink.



### Specifications:

#### Pools up to 12,000 Gallons

PureLink Power Center:	Model 6613AP700, 6614AP700
PureLink Cell Kit:	Model PLC700
AquaLink RS Input:	120 VAC; 60 Hz; 3 amps
RS Contact Rating:	High Voltage - 25 amps; 3HP @ 240 VAC; 1500 Watts Incandescent
	Low Voltage - Class 2, 1 amp @ 24 VAC
AquaPure Input:	115 VAC, 50/60 Hz, 1.5 amps
	230 VAC, 50/60 Hz, 0.75 amps
AquaPure Output:	22-30 VDC @ 3 amps max.
Chlorine:	0.625 lb./24 hr. (283 gm/24 hr.)

#### Pools up to 40,000 Gallons

PureLink Power Center:	Model 6613AP1400, 6614AP1400
PureLink Cell Kit:	Model PLC1400
AquaLink RS Input:	120 VAC; 60 Hz; 3 amps
RS Contact Rating:	High Voltage - 25 amps; 3HP @ 240 VAC; 1500 Watts Incandescent
	Low Voltage - Class 2, 1 amp @ 24 VAC
AquaPure Input:	115 VAC, 50/60 Hz, 2.5 amps
	230 VAC, 50/60 Hz, 1.25 amps
AquaPure Output:	22-30 VDC @ 6 amps maximum
Chlorine:	1.25 lb./24 hr. (567 gm/24 hr.)

PureLink Standard Power Center Dimensions: 13.5" h X 14.5" w X 6.25" d  
 PureLink Sub-panel Power Center Dimensions: 20" h X 14.5" w X 6.25" d  
 Sold Separately: PLC Cell Kit & AquaLink RS Control System



### ALL JANDY PRODUCTS WORK SEAMLESSLY TOGETHER

Jandy Control Systems manage our complete line of technologically advanced products.



Pumps • Filters • Heaters • Heat Pumps  
 Controls • Lights • Water Purification Systems • Valves  
 Water Features • Cleaners • Accessories

